

LINEAR MOTOR

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to a linear motor, and more particularly, to a linear motor having a plurality of permanent magnets assembled with a shaft which is moved rotatably and linearly.

10

Description of the Background Art

~~Figure 1 is a sectional view of a linear motor in accordance with a conventional art, and Figure 2 illustrates arrangement of permanent magnets of the linear motor of Figure 1 in accordance with the conventional art.~~

Generally, as shown in the drawings, a linear motor includes a stator 1 and a rotor 2.

~~The stator 1 includes an outer case 1a, a first armature coil part 1b installed inner side of the outer case 1a, a second armature coil part 1c installed at one side of a support member 1d.~~

~~The rotor 2 includes a shaft 2b and permanent magnets 2a arranged in a checked pattern at an outer~~

09761593 011304

Ins
a1

Ins
a2

~~circumferential surface of the shaft 2b~~

*Ins.
a2
amt.*

~~The first armature coil part 1b is wound in an~~
annular type at the inner side of the stator 1, and the
second armature coil part 1c is also wound in the same
5 annular type as that of the first armature coil part 1b
at the inner side of the stator 1 but arranged in a
checked pattern in a perpendicular direction to the
first armature coil part 1b.

The first armature coil part 1b is linearly moved,
10 while the second armature coil part 1c assembled in the
direction perpendicular to the first armature coil parts
1b is rotatably moved. And, the first armature coil part
1b and the second armature coil part 1c are formed of
three-phase (U, V, W, U', V', W') coils.

15 However, in the case that the first and the second
armature coil parts 1b and 1c adopt the three phases, in
the conventional linear motor, the plurality of
permanent magnets corresponding to the first armature
coil part, that is, the linear movement portion, and the
20 second armature coil part, that is, the rotation
movement portion, are arranged and assembled in a
checked pattern on the outer circumferential surface of
a single shaft. Thus, when the shaft is linearly moved,
~~it is difficult to precisely control the shaft due to~~

09761592-011304

*Ins.
a2
cancel.*

~~the permanent magnets in the checked pattern in addition, since assembling the permanent magnets in the checked pattern is very difficult, its operation efficiency is degraded.~~

5

SUMMARY OF THE INVENTION

*Ins.
a3*

~~Therefore, an object of the present invention is to provide a linear motor in which a plurality of permanent magnets arranged and assembled on the outer circumferential surface of a shaft are divided into a first permanent magnet part, a linear movement zone, and a second permanent magnet part, a rotation movement zone, in a manner of being corresponded to a first armature coil part and a second armature coil part as divided into a rotation movement zone and a linear movement zone, to thereby precisely control linear movement thereof~~

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, there is provided a linear motor including: an outer case; a stator installed at the inner side the outer case and having a first and a second armature coil parts; a first to a ~~third shafts assembled in the inner side of the first~~

*Ins.
a3
mcd.*

~~and the second armature coil parts of the stator; a first permanent magnet part having a plurality of permanent magnets assembled in a ring-type at the outer circumferential surface of the first shaft; and a second~~
 5 ~~permanent magnet part having a plurality of permanent magnets assembled at the outer circumferential surface of the third shaft.~~

The foregoing and other objects, features, aspects and advantages of the present invention will become more
 10 apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

15

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention
 20 and together with the description serve to explain the principles of the invention.

In the drawings:

*Ins.
a4*

~~Figure 1 is a sectional view of a linear motor in accordance with a conventional art;~~

09761593-014904

Figure 2 illustrates arrangement of permanent magnets of the linear motor of Figure 1 in accordance with the conventional art;

Figure 3 is a sectional view of a linear motor in accordance with the present invention;

Figure 4A is a perspective view of a stator of the linear motor of Figure 3 in accordance with the present invention;

Figure 4B is a perspective view of a rotor of the linear motor of Figure 3 in accordance with the present invention;

Figure 5A is a side-sectional view of the stator of the linear motor of Figure 3 in accordance with the present invention; and

Figure 5B is a side-sectional view of the rotor of the linear motor of Figure 3 in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

20

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

~~Figure 3 is a sectional view of a linear motor in~~

FOIA b 7 - D

Ins.
a5

*Ins.
a5
cancel.*

~~accordance with the present invention, Figure 4A is a perspective view of a stator of the linear motor of Figure 3 in accordance with the present invention, Figure 4B is a perspective view of a rotor of the linear motor of Figure 3 in accordance with the present invention, Figure 5A is a side-sectional view of the stator of the linear motor of Figure 3 in accordance with the present invention, and Figure 5B is a side-sectional view of the rotor of the linear motor of Figure 3 in accordance with the present invention.~~

As shown in Figure 3, a linear motor of the present invention includes a stator 10 and a rotor 20.

With reference to Figures 3 and 4A, the stator 10 includes a first armature coil part 12 disposed at one side of an outer case 11 and a second armature coil part 13 disposed at a predetermined distance from the first armature coil part 12.

*Ins.
a6*

~~The first armature coil part 12 and the second armature coil part 13 are formed in a similar structure to that of the armature coil parts of the conventional linear motor.~~

Namely, the first armature coil part 12 is disposed in the annular type to fit the outer case 11, and the second armature coil part 13 is assembled in the

FOI b6 b7C b7D

*Ins. Age
amcl.*

~~outer case 11 in the perpendicular direction to the~~
first armature coil part 12. A reference numeral 14 of
Figure 3 denotes a support member.

With reference to Figures 3 and 4B, the rotor 20
5 includes a first through a third shafts 21, 22 and 23
insertedly disposed in the outer case 11, a first
permanent magnet 21a disposed in a ring type on the
outer circumferential surface of the first shaft 21 and
a second permanent magnet 23a disposed on the outer
10 ~~circumferential surface of the third shaft 23.~~

The first and the second permanent magnet 21a and
23a are positioned to be corresponded to the first and
the second armature coil parts 12 and 13, respectively.

*Ins. Age
a7*

~~The reason why the rotor is sectioned into the~~
15 first through the third shafts 21, 22 and 23 is to
indicate a linear movement zone, a neutral zone, and a
rotation movement zone.

As shown in Figures 4B and 5A, N pole, S pole, N
pole and S pole of the first permanent magnet 21a are
20 arranged in a ring type on the outer circumferential
surface of the first shaft 21 in the horizontal
~~direction in the linear movement zone.~~

The N pole, S pole, N pole and S pole of the
second permanent magnet 23a are arranged on the outer

09764592-011010

circumferential surface of the third shaft 23 in the vertical direction in the rotation movement zone.

*Ins-1
a8-1
cont.*

~~There is formed the neutral zone between the first~~
 permanent magnet 21a and the second permanent magnet 23a,
 5 having a predetermined interval therebetween. The
 neutral zone corresponds to the second shaft 22 as shown
 in Figure 4B.

As to the linear motor of the present invention constructed as described above, since the rotor 20 is
 10 formed to be coaxial with the first through the third
 shafts 21, 22 and 23, its precision can be drastically
 improved compared with that of the conventional linear
 motor.

In other words, in case of the conventional linear
 15 motor, the shaft for the linear movement zone and the
 shaft for the rotation movement zone are junctioned for
 use, but comparatively, in case of the linear motor of
 the present invention, the plurality of permanent
 magnets formed on the outer circumferential surface of
 20 the shaft are divided into the first permanent magnet
 21a, the linear movement zone, and the second permanent
 magnet 23a, the rotation movement zone, and the first
 permanent magnet 21a is formed in a ring type to be
 assembled, so that controlling of the linear movement of

FOR "CONFIDENTIAL"

Ins. as amended.

~~the linear motor, which is moved rotatably and linearly,~~
 can be improved. In addition, the permanent magnet to be
 assembled in the rotation movement zone of the shaft can
 be attached later.

5 As so far described, according to the linear motor
 of the present invention, the first permanent magnet and
 the second permanent magnet are separately constructed
 on the outer circumferential surface of the shaft to be
 assembled, so that the linear movement of the linear
 10 motor can be precisely controlled when the linear motor
 is linearly moved, and the permanent magnet to be
 assembled at the rotation movement zone can be attached
 later.

As the present invention may be embodied in
 15 several forms without departing from the spirit or
 essential characteristics thereof, it should also be
 understood that the above-described embodiments are not
 limited by any of the details of the foregoing
 description, unless otherwise specified, but rather
 20 should be construed broadly within its spirit and scope
 as defined in the appended claims, and therefore all
 changes and modifications that fall within the meets and
 bounds of the claims, or equivalence of such meets and
 bounds are therefore intended to be embraced by the

05761599 031301

appended claims.

0476453-0180
FOOTNOTES